

CABLE COAXIAL 90% 75 OHM RG-6 CHAQUETA NEGRA PVC

PRODUCT DESCRIPTION:

**BONDED LAMINATED ALUMINUM TAPE,90%BRAID,
PVC JACKET**

CENTER CONDUCTOR:

**18 AWG COPPER-CLAD STEEL
NOMINAL DIAMETER:0.040"(1.02 mm)**

DIELECTRIC:

**GAS EXPANDED POLYETHYLENE
NOMINAL DIAMETER OVER DIELECTRIC:0180"**

SHIELD:

**1ST SHIELD: LAMINATED ALUMINUM TAPE BONDED TO
THE DIELECTRIC
NOMINAL DIAMETER OVER TAPE: 0.187" (4.75 mm)**

**2nd SHIELD: 34 AWG ALUMINUM BRAID WIRE
90% COVERAGE**

JACKET:

**PVC
NOMINAL DIAMETER OVER JACKET:0.72" (6.91 mm)
NOMINAL JACKET THICKNESS:0.030" (0.76 mm)**



ELECTRICAL PROPERTIES:

IMPEDANCE: 75.0 +/-3.0 Ohms
VELOCITY OF PROPAGATION: 85.0%NOMINAL
ATTENUATION:@ 68°F(20°C)

@Frequency MHz	dB/100 ft. (MAX.)	dB/100 meters (MAX.)
5 MHz	0.58 dB	1.90 dB
55 MHz	1.60 dB	5.25 dB
83 Mhz	1.95 dB	6.40 dB
187 Mhz	2.85 dB	9.35 dB
211 Mhz	3.05 dB	10.00 dB
250 Mhz	3.30 dB	10.82 dB
300 Mhz	3.55 dB	11.64 dB
350 Mhz	3.85 dB	12.63 dB
400 Mhz	4.15 dB	13.61 dB
450 Mhz	4.40 dB	14.43 dB
500 Mhz	4.66 dB	15.29 dB
550 Mhz	4.90 dB	16.08 dB
600 Mhz	5.10 dB	16.73 dB
750 Mhz	5.65 dB	18.54 dB
865 Mhz	6.10 dB	20.01 dB
1000 MHz	6.55 dB	21.43 dB